



Comfort and intelligence in air conditioning®

Features: **R-410A** / **R-22**
REFRIGERANT / REFRIGERANT

- Auto air swing
- 24V signal control
- Wireless remote control
- Wired remote control (optional)
- Detachable and washable grille
- Durable washable filter
- R-410A / R-22 refrigerant



TECHNICAL SPECIFICATIONS					
Model		CF41B-024-MYH1C	CF41B-036-MYH1C	CF41B-048-MYH1C	CF41B-060-MYH1C
Power supply		208/230V~50/60Hz/1Ph			
Cooling capacity	BTUH	24,000	36,000	48,000	60,000
Air Flow Volume	m ³ /h	1100	1100	2100	2100
	CFM	647	647	1235	1235
Current	A	0.32	0.32	1.6	1.6
Sound pressure level	dB (A)	50	50	57	57
Connecting Pipe Diameter (Gas)	Inches	5/8"		3/4"	
Connecting Pipe Diameter (Liquid)	Inches	3/8"		1/2"	
Net Weight	kg	32	35	50	50
Gross Weight	kg	41	42	59	59
Dimensions (W x H x D)	mm	1300X600X188		1590X695X238	
Packing dimensions (W x H x D)	mm	1345X665X210		1650X760X380	
Container loading quantity	40'GP/40'HC	297/336		126/135	



Carrier InterAmerica Corporation
Miami, Florida USA
www.ciac-comfort.com

Authorized Dealer: